

ALUMINUM LEVEL BASE FRAME

INSERT STYLE:

INSERT COLOR:

CATALOG NUMBER: G1

PART NUMBER:

EXTERIOR CARPET
G1EC
19C005XXX

HEAVY-DUTY CARPET
G1HC
19C010XXX

CARPET
G1CP
19C008XXX

VINYL
G1V
19V002XXX

VINYL-ABRASIVE
G1VA
19A003XXX

SERRATED ALUM. INSERT
G1SAI
19A001XXX

POURED ABRASIVE INSERT
G1PA
19M002XXX

SERRATED ALUMINUM RAIL
G8
16A065000

DIM 'A' WIDTH

1/2" [12.7mm]

#14 X 1" SELF TAPPING STL PLT SCREWS
3 PER CORNER, 2 PER END (90H036002)

DIM 'B' LENGTH
TRAFFIC DIRECTION

1 3/16" [30.2mm]

1/16" [1.6mm]

1 1/2" [38.1mm]

3/4" [19.1mm]

1/2" [12.7mm]

EXTRUDED ALUMINUM RAIL (16A010XXX)

1 13/16" [46.0mm]

OPTION #2

LEVEL BASE FRAME WITH CONTINUOUS ALUMINUM ANCHOR (16A008XXX)

SECTION Y-Y

1" [25.4mm] LONG VINYL CUSHION 24" O.C. [609.6mm] (16V007136)

DIM 'A' WIDTH

1/16" [1.6mm]

ALUMINUM KEY BAR 10" [254mm] O.C. (16A006XXX)

1/2" [12.7mm]

SECTION X-X

1/2" [12.7mm]

TYPICAL PLAN VIEW

NOTES:

*GRIDS OVER STRUCTURES @ 32" O.C. TO SUPPORT A MAX LOAD OF 400 LBS PER SQ. FT. ALL GRIDS WITH LEVEL BASE FRAME TO SUPPORT A 400 LB. ROLLING LOAD. LARGER LOADING MAY BE ACCOMMODATED. CONTACT AFM SALES WITH SPECIFIC LOADING REQUIREMENTS.

*PLEASE VERIFY TRAFFIC DIRECTION.

*MAXIMUM SINGLE GRID SIZE NOT TO EXCEED 12'-0" [3.6M] IN WIDTH (DIM "A").

*ALL SURFACES IN CONTACT WITH MASONRY ARE TO RECEIVE A COAT OF ZINC CHROMATE PRIMER.

*MITERED FRAME CORNERS ARE NOT AVAILABLE.

*WITH OPTION #2, THE ANCHOR LEG IS CUT OFF TO ALLOW FOR MOUNTING IN A FORMED PIT.

*DUE TO 1 1/2" MODULE OF THIS MAT, INSIDE OF FRAME DIMENSION SHOULD BE CHANGED ONLY IN INCREMENTS OF 1 1/2" [38.1mm] TO AVOID THE USE OF FILLER BARS.

*ADDITIONAL SPECIFICATIONS ARE CONTAINED IN THE LATEST AMERICAN FLR MATS INFO PACKET AND ARE CONSIDERED PART OF THIS TRANSMITTAL.

PLEASE VERIFY ALL

QTY

MARK #

LOCATION

MODEL

DIM 'A' WIDTH

DIM 'B' TRAFFIC DIR

FINISH

REMARKS

AMERICAN FLOOR MATS, INC

PROJECT:

LOCATION:

CONTRACTOR:

AGENT:

SHT:

DRG. BY:

DATE:

JOB NO.:

[illegible]