

Checkered Pattern Entrance Mats



Good Better Best Superior



dual fiber surface of scraping and looped pile drying yarns in a mini checkered pattern to absorb moisture and scrape dirt and debris from foot traffic. Color combinations blend light and dark colors to help camouflage debris while maintaining its contemporary appearance.

Test	Test Description	*Results
Abrasion Resistance ASTM D3884-01	Test specimen is subjected to the rubbing action of two abrading wheels under controlled conditions. Results measured in Weight loss (Grams)	1.44
Accelerated Wear	Test specimen is subjected to the action of rollers under a specified load. Sample is rotated 10° after each pass. Results measured in thickness loss (%)	22.73%
Accelerated Soiling ASTM D6540-00	Test specimen is subjected to an accelerated soiling process, for a predetermined length of time. The sample is vacuumed, rated, submitted to an extraction device, then rated again.	(Based on visual inspection) 3.5 - Vacuum Rating 4 - Rating After Extraction
Water Retention	Test specimen is submerged in water for 5 minutes, removed, drained for 15 seconds and weighed. Results measured in weight gain. (Gallons per sq. yd.)	.06
Flammability ASTM D2859 (CPSC FF 1-70)	Intended to measure the matting's response to an ignition source in a controlled environment. The uncharred area of the test specimen must be greater than 1 inch to pass.	3.6 Inches

*All testing of floor matting has been performed by an independent testing laboratory.

AATCC Rating Key (For Accelerated Soiling Test)	
5	No change
4	Slight change
3	Noticeable change
2	Considerable change
1	Severe change

- Face Weight: 26 oz. per sq. yd.
- Thickness: 5/16"
- Vinyl Backing reduces mat movement
- Stock Sizes: 2' x 3', 3' x 4', 3' x 5', 3' x 6', 3' x 10', 4' x 6', 4' x 8'
- Roll Sizes: 3' x 60', 4' x 60', 6' x 60'
- Custom Sizes available in 3', 4', and 6' widths



Custom Lengths

