AMERICAN ~FLOOR MATS walk well 152 Rollins Avenue #102

Rockville, MD 20852 800-762-9010 240-780-3309 (fax) http://www.americanfloormats.com

Deep Freeze Walk-in Freezer Kitchen Mats



General Information:

3/8" thick Black Nitrile Rubber High Density Closed Cell Foam

Features:

- Constructed of 100% high density, closed cell Nitrile rubber for maximum resistance to water, greases, chemicals, and animal fats.
- The only rubber mat specifically formulated to perform in deep-freeze environments.
- Features a raised knob solid top surface to enhance traction.
- Tested to withstand temperatures to -40° Fahrenheit (approximately -40° Celsius).
- Lightweight, out performs thicker, heavier mats and is easy to clean by pressure washing or hosing off.
- These mats are reversible to extend service life.
- Overall thickness: 3/8" (Low profile for easy cart access).
- Contains MicroStopTM, a unique anti-microbial compound made from a specially formulation that inhibits the growth of micro-organisms such as bacteria and fungi that can cause odor, stains and product deterioration. MicroStopTM is incorporated directly into the mat during the manufacturing process so it cannot be washed off or wear away over time.
- ASTM C 1028-96 Static Coefficient of Friction: Dry 0.94 Wet 0.69
- Anti-static: Electrical Resistance IBM (Surface to Ground) ASTM F-150 NFPA 99 Chapter 12 Section 4.1.3.8 (6)(7), 1990. Average Electrical Resistance at 700 F. and 50% Relative Humidity: 1.7 x 10 9th
- Passes Flammability Standard DOC-FF-1-70
- Tabor Abrasion: 1% lost @ 1,000 cycles per Fed. Std. 191
- Durometer: 50 to 55 Shore A
- U.V. Stable