

Interlocking Garage Tiles

Installation Instructions & Cleaning and Maintenance

INSTALLATION

PREPARATION

- All Interlocking Garage Tiles must be acclimated to room temperature for 24 hours prior to installation. During this period room temperature should be maintained between 65° - 85° F.
- Remove as much equipment as possible from the work area.
- Thoroughly sweep floor area and remove any debris.
- Fill any significant holes or cracks in the floor.

INSTALLATION

- Install tiles from the corner of the room working across and down (like reading a book: across each row and then down to the next one).
- Once all the full tiles have been installed then proceed with the tiles that need trimming.
 - The tiles can be easily cut with a sharp utility knife or jigsaw to fit around walls, furniture and support beams. For larger jobs, the use of a band saw or table saw may make cutting easier.
 - A space of at least 1/4" (6mm) should be left at the walls and any other obstacle to allow the tiles room for expansion.
 - If needed, this gap can be filled with a flexible caulk and/or covered with cove base).
- In most applications no gluing is required. However, it is recommended when:
 - There is extremely heavy traffic over the tiles combined with frequent, tight turns.
 - The tiles will be exposed to very high or very low temperatures.
- When gluing is required for best results we recommend the use of Garage TileBond.

CLEANING & MAINTENANCE

CLEANING

- As with any type of flooring, regular cleaning will maintain the tile's attractive appearance and ensure maximum life. Regular, light cleaning is preferable to infrequent, heavy cleaning.
- After the floor is swept, a mop and any general purpose cleaning detergent may be used to clean Interlocking Garage Tiles. However, in order to obtain best results and maximum life, we recommend using a micro fiber mop with a neutral PH cleaning detergent such as "Fabuloso all purpose cleaner". For larger areas a cylindrical scrubber dryer may be used.

MAINTENANCE

- Although Interlocking Garage Tiles are resistant to oil and most chemicals it is prudent to remove any oil or other chemicals as soon as possible.