

Super Brush Matting

Synthetic Alternative to Cocoa Mat
 Without The Shedding
 Available 6'7" & 13'2" Roll Widths

PRODUCT SPECIFICATIONS

PRODUCT COMPOSITION	STANDARD/NORMS	DATA
Manufacturing Process	ISO 2424	Needle Punched
Pile yarn composition	CEE 83/623	100% Solution-Dyed UV Stabilized Polypropylene Fibers
Primary Backing	ISO 2424	High Density Rubber
PRODUCT DIMENSIONS		
Pile Height (+ or -0.5mm)	ISO 1766	.31 inches
Total Height (+ or -7.5%)	ISO 1766	.56 inches
Pile Weight (+ or -7.5%)	ISO 8543	50.1 oz/sy
Total Weight (+ or -7.5%)	ISO 8543	82 oz/sy
Total Size (+ or -0.2%)	ISO 3018	
ELECTROSTATIC PROPERTIES		
Dimensional Stability	EN 986 / ISO 2551	Pass
Walk on test	ISO TR 6356	< 2 KV
Sound Insulation	ISO 140-8	>= 24 dB
COLOR FASTNESS		
To Light	ISO 105 B02	>=6
To Water	ISO 105 E01	4
To Shampoo	BS 1006 UK-TB	4
To Rubbing dry & wet	ISO 105 x 12	4-5
FLAMMABILITY RATING		
Optical Smoke Density	ASTM E662	Pass
Pill Test (Surface Flammability)	ISO 6925 / ASTM D2859/ CPSC FF 1-70	Passes Federal Flammability Standard

INSTALLATION

Floor area should be completely clean, dry, and free of foreign substances. Use a floor leveler as needed to ensure floor is smooth, even and without cracks. Our matting products can be cut easily to any size, shape or pattern with a utility knife. Follow adhesive manufacturer's instructions.

Adhesive (if applicable): Multi-Bond Mat Adhesive, or approved equal.

CLEANING & MAINTENANCE

Daily: Vacuum daily with a commercial grade vacuum cleaner that features a rotary power brush or beater bar. Mats release more soil when completely dry.

Periodic Maintenance: Our matting products clean beautifully with the use of a Hot Water Extraction machine. Minimum quarterly intervals recommended for high traffic applications. For optimum performance during winter months, traffic lanes may require more frequent extraction cleaning depending on weather conditions and climate.

WARRANTY

Limited 3-Year Abrasive Warranty. limited warranty for abrasive wear on indoor installations. Warranty requires product installation over a dry, smooth, hard, flat surface free of cracks and foreign substances. Product must be installed using the appropriate adhesive, or approved equal. Product must be maintained according to maintenance instructions.

American Floor Mats
 152 Rollins Avenue #102
 Rockville, Maryland 20852

800-762-9010 (toll-free) / 301-881-7840 (fax)

www.americanfloormats.com / help@americanfloormats.com