


Vinyl Link Logo Mats: Specifications



Mat Sizes:	All Custom Made
Link Size:	1/2" W x 2' H
Thickness:	7/16" D
Opening Between Links:	Close Weave: 1/2" H x 1/16" H (Heel-Proof, ADA-Complaint)
Weight:	~2.3 Lbs/SqFt
Flammability:	Class 1 (ASTM E-648 and NFPA)
Static Coefficient of Friction:	Dry, 0.67; Wet, 0.89 (ASTM D-2047-82)
Nosing:	Beveled (for Surface Installation); Square (for Recessed Installation)
Minimum Text Size:	4" W x 5" H
Color Stay:	Will Not Fade, Stain or Wear Off

USE:

Vinyl Link Logo Mats clean shoes and boots and are most commonly found in entrances, vestibules and lobby areas. Debris and moisture fall between the vinyl links keeping the surface more slip-resistant and helping prevent dirt from being tracking inside.

CONSTRUCTION:

Vinyl Link mats retain their vibrant colors, are reversible and are made for high-traffic / heavy-duty use. These mats are furnished with matching or contrasting color nosing which is attached on all 4 sides. 2" beveled nosing is used for surface mounted mats. 1-1/2" square nosing is used for recessed mats or mats butted one to another or to a square border such as a wall. Mats equipped with square nosing only are completely reversible.

Extruded vinyl links woven on rust-resistant galvanized 13 gauge spring steel wire with tempered reinforcing metal bar on the front and back edges and with nosing on all 4 sides (mitered and sealed corners).

Wires should run the short dimension of mat; same cleaning action whether traffic moves parallel or perpendicular to wires. Individual links have extra weight at stress points and extra strong ribs for cleaning action.