

# Chevron Entrance Mats

## Specifications

### General Information:

#### Surface

Fiber Type:	Polypropylene
Weight:	18 ozs/sqyd
Carpet Height:	1/4"
Design:	Ridge Construction

#### Backing

Type:	100% PVC Vinyl
Thickness:	1/8" – Border; 3/8" Total Thickness
Durometer:	60

### Features:

- Polypropylene surface material is constructed to resist crushing, maintain performance and extend product life.
- Border is designed to help contain water and dirt on mat keeping them off carpets and floors.
- Polypropylene surface removes and traps dirt and moisture and holds it on mat, between ridges so it is not tracked in.
- Vinyl backing helps to minimize mat movement and improves traction on hard surfaces.
- Durable anti-static Polypropylene face suitable for indoor or outdoor use.
- Polypropylene fibers dry quickly preventing fading and rotting. Material is stain and mildew resistant.
- Easy to clean: Just vacuum or hose off and hang to dry.
- Not adversely effected by salt or ice melt.
- Should not be used in areas exposed to animal fats (kitchens) or petroleum products.
- Anti-static: Ribbed Entrance Mats have a maximum average voltage of 1.6 KV as measured by the AATCC 134 Electrostatic Propensity Test and meets IBM's minimum standard for electrical resistance (NFPA99).
- ASTM C 1028-89 Static Coefficient of Friction Dry 0.68