

Comfort Drainage Anti-Fatigue Mats

Specifications



General Information:

TYPE: Nitrile Rubber High Density Closed Cell Foam (10% Recycled Content)

THICKNESS: 9/16"

DUROMETER: 50 to 55 Shore A

Features:

- Provides superior anti-fatigue properties for employee comfort and ergonomic benefits.
- Constructed of 100% high density, closed cell Nitrile rubber cushion for maximum resistance to water, greases, chemicals, and animal fats.
- Lightweight, out performs thicker, heavier mats and is easy to clean by pressure washing or hosing off.
- Available with or without holes.
- Slip resistant surface helps to reduce slip and fall accidents. Liquids and debris flow easily through the holes away from shoes.
- ASTM C 1028-96 Static Coefficient of Friction: Dry - 0.94 Wet - 0.69
- Anti-static: Electrical Resistance – IBM (Surface to Ground) ASTM F-150 NFPA 99 Chapter 12 Section 4.1.3.8 (6)(7), 1990. Average Electrical Resistance at 700 F. and 50% Relative Humidity: 1.7×10^9 th
- Passes Flammability Standard DOC-FF-1-70
- U.V. Stable
- Welding safe
- Treated with an anti-microbial agent
- Safe to autoclave for sterilization