

Dual Density Entrance Mats

Specifications

General Information:

Surface

Fiber Type:	Solution Dyed Continuous Filament Decaloon Loop Pile and Loop Scraper Yarns
Weight:	26 ozs/sqyd
Total Height:	3/8"
Design:	Loop Pile Construction
Twist:	Each strand of yarn contains fibers that have been twisted individually 6 turns per inch and then twisted together at 6 turns per inch. The yarn is then heat set to permanently maintain the hard twist.

Backing

Type:	Vinyl
Thickness:	0.094" – Border; 0.052" – Body
Durometer:	60

Features:

- Continuous filament resists crushing, which maintains high performance and extends product life.
- Loop pile construction traps dirt, debris and moisture from foot traffic.
- Vinyl border is not to be a tripping hazard and is ADA compliant.
- Vinyl backing: minimizes movement and improves traction on hard surfaces.
- Indoor/Outdoor: Durable anti-static face suitable for indoor or outdoor use.
- Fibers dry quickly preventing staining, fading and rotting.
- Easy to clean: Just vacuum or hose off and hang to dry. Mats can also be steam extracted.
- Colorfast: Solution dyed for excellent light and wet fastness.
- Not adversely effected by salt or ice melt.
- ASTM C 1028-89 Static Coefficient of Friction Dry .70
- Abrasion Resistance of 1.27g using test ASTM D3884-01.
- Accelerated Wear Test: 13.91%
- Accelerated Soiling of 4.5 (vacuum rating) and 5 (extraction rating) per test ASTM D6540-00.
- Water Retention of 0.50 Gallons/SY.
- Flammability rating of 3.6in per test ASTM D2859 (CPSC FF 1-70).