

# Miners Moss Prospecting Mats

## Specifications

### General Information:

#### Surface

Fiber Type:	Extruded Vinyl
Weight:	20 ozs/sqyd
Nub Height:	7/16"
Design:	Random Loop Construction
Overall Weight:	0.50 lbs/sqft

### Features:

- 100% extruded vinyl surface material is constructed to resist crushing, maintain performance and extend overall product life.
- Vinyl surface removes and traps dirt and debris and holds it on mat, between ridges.
- Durable anti-static extruded vinyl suitable for indoor or outdoor use.
- Vinyl fibers dry quickly preventing fading and rotting. Material is stain and mildew resistant.
- Easy to clean: Just shake out or hose off and air dry.
- Not adversely effected by salt or ice melt.
- Should not be used in areas exposed to animal fats (kitchens) or petroleum products.
- Passes Flammability Standard DOC-FF-1-70.
- Anti-static: Vinyl Mesh Mats have a maximum average voltage of 1.6 KV as measured by the AATCC 134 Electrostatic Propensity Test and meets IBM's minimum standard for electrical resistance (NFPA99). Vinyl Mesh Mats are safe for use in computer rooms and around electronic equipment.
- ASTM C 1028-89 Static Coefficient of Friction Dry 0.68.