

Super Ribbed Entrance Mats

Specifications

Product Description

Material 100% solution-dyed UV stabilized polypropylene fibers
 Backing High density rubber
 Roll Sizes 6' 7" x approximately 82'; 13' 2" x approximately 68' 8"
 Custom Sizes 6' 7" x custom lengths up to 82'; 13' 2" x custom lengths up to 68' 8"

Technical Specifications

Product Dimensions

Pile Height	ISO 1776	in Inches	5 / 32"
Total Height	ISO 1776	in Inches	3 / 8"
Pile Weight	ISO 8543	In Ounces per Square Yard	33.9 oz/sq yd
Total Weight	ISO 8543	In Ounces per Square Yard	64 oz/sq yd

Safety

Surface Flammability	ASTM D2859 CPSC FF 1-70	Test specimen must be greater than 1" in at least 7 of 8 specimens tested	Passes
----------------------	----------------------------	---	--------

Performance

Static Electrical Propensity	EN 1815	Antistatic: less than 2 kilovolts (kV)	< 2 kV
------------------------------	---------	--	--------

Color Fastness

to Light	ISO 105 B02	1 = considerable change; 5 = negligible or no change	5
to Water	ISO 105 E01	1 = considerable change; 5 = negligible or no change	5
to Shampoo	BS 1006 1	1 = considerable change; 5 = negligible or no change	4.5
to Rubbing Wet & Dry	ISO 105 x 12	1 = considerable change; 5 = negligible or no change	Wet = 3.5; Dry = 4

LEED

MR Credit 4	LEED-NC v. 3	For 1 - 2 points: \$ value of all materials = min. average 10% recycled content	15% post consumer recycled
IEQ Credit 4.1	LEED-NC v. 3	Low-emitting adhesive with a VOC of 50 g/L or less for indoor carpet adhesive	Multi-Bond VOC: 0 g/L
IEQ Credit 4.3	LEED-NC v. 3	For 1 point: low-emitting flooring per GreenLabelPlus or FloorScore	GreenLabelPlus certified
IEQ Credit 5	LEED-NC v. 3	For 1 point: semi-permanently installed entrance system at least ten feet in length and maintained on a weekly basis by a contracted service organization.	Super Ribbed Mat is designed for semi-permanent installation

