

Waterhog Classic Floor Mat Tiles

Specifications

General Information:

Surface

| | |
|-----------------|--|
| Fiber Type: | Solution Dyed Polypropylene, outstanding lightfastness |
| Face Weight: | 24 ozs/sqyd |
| Total Weight: | 135 ozs/sqyd OR 240 ozs/sqyd |
| Nub Height: | 1/4" OR 7/16" |
| Tiles per Case: | 12 OR 10 |
| Design: | Square "Waffle" |

Backing

| | |
|------------|---|
| Type: | 100% SBR Rubber (20% Recycled Content) |
| Thickness: | 0.110" – Border; 0.190" Nubs; 0.050" – Between Nubs |
| Durometer: | 60 |

Features:

- Reinforced face NUBS: Face NUBS are reinforced with rubber to resist crushing, maintaining high performance and extending product life.
- Raised NUB surface: Removes and traps dirt and moisture and holds it on mat below shoe level so it is not tracked in.
- Smooth backing: Must be glued down with floor adhesive.
- Rubber backing: Lays flat, will not crack or curl like vinyl mats.
- Indoor/Outdoor: Durable anti-static polypropylene face suitable for indoor or outdoor use.
- Polypropylene fiber system dries quickly preventing fading and rotting.
- Easy to clean: Just vacuum, spray down or steam extract.
- Colorfast: Solution dyed for excellent light and wet fastness.
- Not adversely effected by salt or ice melt.
- Should not be used in areas exposed to animal fats (kitchens) or petroleum products.
- Passes Flammability Standard DOC-FF-1-70
- Anti-static: Waterhog mats have a maximum average voltage of 1.6 KV as measured by the AATCC 134 Electrostatic Propensity Test and meets IBM's minimum standard for electrical resistance (NFPA99). Waterhog mats are safe for use in computer rooms and around electronic equipment.
- ASTM C 1028-89 Static Coefficient of Friction Dry .70