

Waterhog ECO Berber Entrance Mats

Specifications

General Information:

Surface

Fiber Type:	Solution Dyed Polypropylene, outstanding lightfastness (100% Recycled Content)
Weight:	36 ozs/sqyd
Nub Height:	3/8"
Design:	Hobnail

Backing

Type:	SBR Rubber (15-20% Recycled Content)
Thickness:	3/8" Nubs; 1/4" – Between Nubs
Durometer:	65

Features:

- Polypropylene surface resists crushing to maintain high performance and extending product life.
- Border is designed to help prevent water and dirt on mat from dropping to the floor. Hobnail pattern allows Waterhog ECO Berber mats to hold up to 1 1/2 gallons of water per square yard.
- Raised NUB surface: Removes and traps dirt and moisture and holds it on mat below shoe level so it is not tracked in.
- Rubber backing: Lays flat, won't crack or curl like vinyl mats.
- Indoor/Outdoor: Durable anti-static polypropylene face suitable for indoor or outdoor use.
- Polypropylene fiber system dries quickly preventing fading and rotting.
- Easy to clean: Just vacuum or hose off and hang to dry.
- Colorfast: Solution dyed for excellent light and wet fastness.
- Not adversely effected by salt or ice melt.
- Should not be used in areas exposed to animal fats (kitchens) or petroleum products.
- Passes Flammability Standard DOC-FF-1-70
- Anti-static: Waterhog mats have a maximum average voltage of 1.6 KV as measured by the AATCC 134 Electrostatic Propensity Test and meets IBM's minimum standard for electrical resistance (NFPA99). Waterhog mats are safe for use in computer rooms and around electronic equipment.
- ASTM C 1028-89 Static Coefficient of Friction Dry .70